

SHIELDS

VENGEANCE WMX1 & WMX2 THREAT LEVEL IIIA AND SPECIAL THREAT TESTED

The WMX1 & WMX2 are original Classic Cut VENGEANCE[™] Series hard armor shield platforms. WMX1 incorporates a tapered lower for deployment in tight or narrow spaces and the WMX2 has a full cut lower for a higher degree of coverage. Both models come standard with our patented VENGEANCE[™] viewport which enhances operator field of view at extreme close quarters. VENGENANCE series shields are deployed by over 2000 United States Marshals as well as hundreds of federal, state and local law enforcement agencies. BlueRidge Armor, Legendary Performance, MISSION

STANDARD FEATURES:

DRIVEN - PURPOSE BUILT!

Size / Weight: 18" x 30" / 11 lb.

20" x 34" / 13 lb. 24" x 36" / 15 lb. 24" x 42" / 17 lb. 24" x 48" / 19 lb.

Patented VENGEANCE™ Viewport

Rigid Carbon Fiber Handle

Large Single Curvature Ballistic Torso Protection Hybrid Composite COREBOND® Structural Ballistics NIJ 0108.01 Rated IIIA and Special Threat Tested

OPTIONAL FEATURES:

- Color Options: Black, Ranger Green, Coyote, Multicam and Multicam Black
- Custom COREBOND® Large Format ID Lettering
- Elzetta TriDextrous or Straight Bar Handle Integrated 1000 Lumen LED
- Fox Fury Straight Bar Handle Integrated 1200 Lumen LED and Remote Pressure Switch
- Fox Fury Auxillary B30 600 Lumen LED Remote Pressure Switch
- Viewport Delete
- · Shield Hook with MOLLE Attachment
- Shield Hook Sling Attachment
- · Carry Bag

SPECIAL THREAT TESTING DATA ON REVERSE SIDE





SHIELDS

VENGEANCE SERIES HARD ARMOR SHIELDS STANDARD BALLISTICS*, SPECIAL THREATS AND TEST METHODS**

VENGEANCE™ VIEWPORT

RIMROCK 44-mag., 240-grain semi-wadcutter gas checked (SWCGC) 1400 ft/s. NIJ 0108.01*

REMINGTON 9-mm, 124-grain full metal jacketed (FMJ) 1400 ft/s. NIJ 0101.08*

WINCHESTER 12-gauge, 2-3/4" MAG., 1 oz. Rifled Slug 1650 ft/s. USMS Ballistic Shield Protocol – Dated 06.05.18

VENGEANCE™ SHIELD BODY

RIMROCK 44mag., 240gr., Semi Wadcutter-Gas Check (SWC-GC) 1400 ft/s NIJ 0108.01*

REMINGTON 9mm 124gr., Full Metal Jacket (FMJ) 1400 ft/s NIJ 0108.01*

GECO 9mm 123gr., Steel-Jacket Lead Core (SJLC) 1380 ft/s (FBI 1" from edge / 3 in 3" Circle) **

SELLIER & BELLOT 9mm Luger 115gr., Full Metal Jacket (FMJ) 1330 ft/s (FBI 1" from edge / 3 in 3" Circle) **

WINCHESTER RANGER SXT 9mm 127gr., +P+ T-Series 1400 ft/s (FBI 1" from edge / 3 in 3" Circle) **

RUAG DM41 9mm Luger 124gr., Steel-Jacket Lead Core (SJLC) 1385 ft/s (3 in 3" Circle) **

HORNADY 5.7x28 27gr., SS195 Lead Free Hollow Point (LFHP) 2086 ft/s (3 in 3" Circle) **

HORNADY 5.7x28, 40gr., Hornady V-Max SS197 (Blue Tip) 1730 ft/s (3 in 3" Circle) **

RUSSIAN 7.62x25 TOKAREV 86gr., Steel-Jacket Lead Core (SJLC) 1590 ft/s (FBI 1" from edge / 3 in 3" Circle) **

WINCHESTER 9mm NATO 124gr., Full Metal Jacket (FMJ) 1445 ft/s (FBI 1" from edge / 3 in 3" Circle) ***

SPEER 44mag 240gr., Semi Jacketed Hollow Point (SJHP) 1400 ft/s WINCHESTER 12-Gauge., 2-3/4" MAGNUM, 1 oz. Slug 1650 ft/s

REMINGTON 9-mm, 124-grain full metal jacketed Submerged in Water 30 Minutes (NIJ 0101.06 Protocol) v50 1914 ft/s

17gr. FSP Submerged in Water 30 Minutes (NIJ 0101.06 Protocol) v50 2014 ft/s

17gr. FSP Ambient v50 2032 ft/s

STAB RATED Edged Blade 2, P1 Single Edged Blade Penetrator and S1 Double Edged Blade E1 & E2


USMS Ballistic Shield Protocol - Dated 06.05.18

*All projectiles were fired from a universal receiver which was fitted with the appropriate barrel and mounted on a NTS-Chesapeake Testing mount.

Ft/s: Projectile Velocity in feet per second. ***FBI specific procedure and projectile. **FBI procedure applied to additional Special Threat Rounds.

VENGEANCE" Series shields with exclusive patent pending viewport and patent pending Elzetta integrated shield lighting have been designed from the ground up utilizing direct input from elite federal, local and state law enforcement agencies. Stab rating abbreviated 0115 testing NTS/ Chesapeake Laboratory. Like no other shields on Earth.





FBI Impact Shot 1" From Edge



